

HX BASE

Broadloom

Construction

Tufted, Textured Loop, Tip Shear

Broadloom Width

13' 6" (4.11 m.)

Yarn Type

Milliken-Certified WearOn® Nylon Type 6,6

Stain Repel / Stain Resist / Soil Release

StainSmart®

Antimicrobial

AlphaSan® AF Built-In Protection†

Bleach Resistance

ColorSeal®

Dye Method

Millitron®

Tufted Face Weight

36 oz/yd² (1,221 g/m²)

Gauge

1/12 (47.2/10 cm)

Stitches Per Inch

12.0 (47.2/10 cm)

Tufts

144/in² (2,228 g/100 cm²)

Finished Pile Height

0.21" (5.33 mm)

Finished Pile Thickness

0.175" (4.45 mm)

Average Density (Finished)

7,323

Standard Backing

PVC-Free Endura-Loc™

Available with Cushion-Loc™ and Moisture-Bloc™

Nominal Total Thickness

0.31" (7.87 mm)

Nominal Total Weight

68.0 oz/yd² (2,306 g/m²)

Flammability (Radiant Panel ASTM-E-648)

≥ 0.45 (Class I)

Smoke Density (NFPA-258-T or ASTM-E-662)

≤ 450

Methenamine Pill Test (CPSC FF-1-70 or ASTM D 2859)

Self-Extinguishing

Lightfastness (AATCC 16E)

≥ 4.0 at 80 Hours

Crocking (AATCC 165)

≥ 4.0 Wet or Dry

Static Electricity (AATCC-134) 20% R.H., 70° F.

≤ 3.5 KV, Permanent Conductive Fiber

Texture Appearance Retention Rating (TARR)

Severe Traffic End-Use Applications

Recommended Maintenance

MilliCare® Textile and Carpet Care Service Network

Indoor Air Quality—CRI Green Label Plus™

GLP2860, Carpet Category 1Y

Recommended Installation Method

Broadloom

WARRANTIES

10 Year Wear / 10 Year Fiber Loss
 Staining/Soiling (StainSmart®)
 Antimicrobial Protection (AlphaSan®)
 Atmospheric Fading
 Delamination of Backing

Edge Ravel
 Flammability
 Antistatic
 Tuft Bind
 Floor Compatibility

Additional warranties if purchased:

Cushion Resiliency (Cushion-Loc™ backing)
 Moisture Barrier (Moisture-Bloc™ backing)



Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.