

Inspired Textures

Ice



Milliken's Inspired Textures products are constructed to add subtle depth and dimensionality to any carpet design while withstanding heavy commercial applications. The combination of two patented Milliken technologies – Millitron® patterning and MYI™ (Multiple Yarn Infusion™) tufting – results in sophisticated textures with handmade randomness and unpredictability unlike any other machine-made carpet.

Construction	Tufted, Multiple Yarn Infusion, Multi-Level Cut & Loop Tip Shear
Dye Method	Digital Millitron® Dye Injection
Face Fiber	Ascend Nylon Type 6,6
Stain and Soil Protectant	StainSmart®
Mold/Mildew Odor Control	AlphaSan® Built-In Protection
Bleach Resistance	ColorSeal®
Tufted Face Weight	36 oz./sq.yd. (1,220.7 g./sq.m.)
Tufting Gauge	3/16 (21.0/10 cm.)
Stitches	13/in. (51.2/10 cm.)
Tufting Density	144/sq.in. (2,230.2/100 sq.cm.)
Finished Pile Height	0.28 in. high/0.13 in. low (7.1/3.3 mm.)
Primary Backing	Synthetic Woven
Secondary Backing	Endura-Loc™
Recycled Content with Endura-Loc	1% Pre-Consumer
Recycled Content with optional attached pad	1% Pre-Consumer, 12% Post-Consumer, 3% Rapidly Renewable
Nominal Total Thickness	0.37 in. (9.4 mm.)
Width	13' 6" (4.11 m.)
Nominal Total Weight	74.4 oz./sq.yd. (2,522.7 g./sq.m.)
Flammability (Radiant Panel ASTM-E-648)	≥ 0.45 (Class I)
Smoke Density (NFPA-258-T or ASTM-E-662)	≤ 450 Flaming and Non-Flaming
Static Electricity (AATCC-134) 20% R.H., 70° F.	≤ 3.5 KV
Texture Appearance Retention Rating (TARR)	Heavy Traffic End-Use Applications
Recommended Maintenance	MilliCare® Textile and Carpet Care Service Network
Indoor Air Quality - CRI Green Label Plus™	GLP8064, Carpet Category 1Y

Optional Features Available:

Secondary Backing - Attached Cushion	Cushion-Loc™ featuring Enhancer™ Technology (500 sq. yd. min.)
Secondary Backing - Attached Cushion w/Moisture Barrier	Moisture-Bloc™ featuring Enhancer™ Technology (500 sq. yd. min.)
Nominal Total Thickness with Attached Cushion	0.49 in. sheared (12.4 mm.)
Nominal Total Weight with Attached Cushion	103.8 oz./sq.yd. (3,519.6 g./sq.m.)

Design © Milliken & Company. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice.



Warranties:

Wear - 10 Year / 10% Fiber Loss
Staining/Soiling (StainSmart®)
Bleach Resistance (ColorSeal®)
Atmospheric Fading
Delamination of Backing
Antimicrobial Protection (AlphaSan®)

Edge Ravel
Flammability
Antistatic
Tuft Bind
Floor Compatibility

Additional warranties if purchased:

Moisture Barrier (Moisture-Bloc™ backing)
Cushion Resiliency (Cushion-Loc™ backing)