

Room Service 32

Milliken's Room Service products are constructed for hotel guestroom environments and come standard with two of Milliken's proprietary enhancement technologies: StainSmart to resist, repel and release stains and soil, and ColorSeal for bleach resistance. No other patterned carpet in the hospitality industry offers the performance attributes that cover all of your carpet concerns. Milliken backs the Performer Series with unmatched warranties for wear, stains, soil and bleach.

| | |
|--|--|
| Construction | Tufted, Patterned Cut Pile |
| Dye Method | Digital Millitron® Dye Injection |
| Face Fiber | Milliken WearOn® BCF Nylon Type 6,6 |
| Stain and Soil Protectant | StainSmart® |
| Mold/Mildew Odor Control | AlphaSan® Built-In Protection |
| Bleach Resistance | ColorSeal® |
| Tufted Face Weight | 32 oz./sq.yd. (1,085.0 g./sq.m.) |
| Tufting Gauge | 1/10 (39.4/10 cm.) |
| Stitches | 10.75/in. (42.3/10 cm.) |
| Tufting Density | 107.5/sq.in. (1,666.6/100 sq.cm.) |
| Finished Pile Height | 0.22 in. sheared (5.6 mm.) |
| Average Density | 5,236 |
| Primary Backing | Synthetic Woven |
| Secondary Backing | Endura-Loc™ |
| Recycled Content with Endura-Loc | 1% Pre-Consumer |
| Recycled Content with attached pad | 1% Pre-Consumer, 13% Post-Consumer, 3% Rapidly Renewable |
| Nominal Total Thickness | 0.30 in. sheared (7.6 mm.) |
| Width | 13' 6" (4.11 m.) |
| Nominal Total Weight | 64.0 oz./sq.yd. (1,625.6 g./sq.m.) |
| Flammability (Radiant Panel ASTM-E-648) | ≥ 0.45 (Class I) |
| Smoke Density (NFPA-258-T or ASTM-E-662) | ≤ 450 Flaming and Non-Flaming |
| Static Electricity (AATCC-134) 20% R.H., 70° F. | ≤ 3.5 KV |
| Recommended Traffic | Hotel Guestrooms |
| Recommended Maintenance | MilliCare® Textile and Carpet Care Service Network |
| Indoor Air Quality - CRI Green Label Plus™ | GLP2860, Carpet Category 1Y |
| Optional Features Available: | |
| Carpet Widths | 9 ft. and 12 ft. (200 square yard minimum for 9 ft. width) |
| Secondary Backing - Attached Cushion | Cushion-Loc™ featuring Enhancer™ Technology (500 sq. yd. min., 9' not available) |
| Secondary Backing - Attached Cushion w/Moisture Barrier | Moisture-Bloc™ featuring Enhancer™ Technology (500 sq. yd. min., 9' not available) |
| Nominal Total Thickness with Attached Cushion | 0.40 in. sheared (10.2 mm.) |
| Nominal Total Weight with Attached Cushion | 98.0 oz./sq.yd. (3,322.9 g./sq.m.) |

Design © Milliken & Company. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice.



Applicable Milliken Warranties:

Wear - 10 Year / 10% Fiber Loss
Staining/Soiling (StainSmart)
Bleach Resistance (ColorSeal)
Atmospheric Fading
Delamination of Backing
Antimicrobial Protection (AlphaSan)

Edge Ravel
Flammability
Antistatic
Tuft Bind
Floor Compatibility

Additional warranties if purchased:

Moisture Barrier (Moisture-Bloc™ backing)
Cushion Resiliency (Cushion-Loc™ backing)